

# STEALTH

## AVAILABLE WITH HEAT!

The Stealth series of portable extractors have a large 17-gallon capacity to handle tough commercial jobs with ease. This unit doubles as a powerful dry vacuum, eliminating the need for two separate pieces of equipment. For the ultimate in productivity, consider the optional factory installed Heat 'N' Run system to deliver 200-degree heat in just 90 seconds! Built with a patented bladder system, the Stealth offers large capacity cleaning in a compact design. A see-through recovery dome allows easy monitoring and access. The most powerful unit uses two power cords and produces maximum pressure and suction, leaving carpets clean and dry in record time. All models come complete with a deluxe dual-jet stainless steel S-bend wand and hose assembly. All heated and other dual-cord units come equipped with a circuit locator.



## FEATURES

- Exclusive clamshell body provides fast and easy internal access for quick servicing.
- Flexible, lift-out bladder.
- "No drip" motor cavity guarantees water spilled on the outside of machine stays out!
- 50 foot detachable power cord.
- Upright-mounted motors with a specially-designed intercooler system guarantee long-lasting life.
- Stair-climbing handle combined with large rear wheels increase maneuverability.
- See-through recovery dome.
- Top-mounted switches.

## OPTIONAL ACCESSORIES

1204AC Powermate—12" wide power brush  
321AC Upholstery Tool  
323AC Prespray wand  
L00814 Cloth Dry Filter Bag

For our full line of optional accessories (1½" diameter), see pages 15-17.

## MODELS

All come complete with 25-ft. hose assembly and dual-jet stainless steel S-bend wand  
All models available with optional HEAT—add "H" to model number (1700SH, etc.)

1700SX Dual hi-perf. 2-stage vacs, 150" lift, 100 PSI  
1700RX\* Dual 3-stage vacs, 180" lift, 150 PSI  
1700LX Dual hi-perf. 2-stage vacs, 150" lift, 500 PSI adjustable  
1700CX\* Dual 3-stage vacs, 180" lift, 500 PSI adjustable  
1700FX Dual hi-perf. 3-stage vacs, 210" lift, 500 PSI adjustable, dual power cords, circuit locator\*\*

\*20 amp circuit required

\*\*Circuit locator included on all heated and other dual cord units

## SPECIFICATIONS

Solution Tank	17 gallon
Recovery Tank	15 gallon
Solution Pressure	100/500 PSI adjustable
Vacuum Motors	Dual 2-stage/Dual 3-stage
Water Lift	150/180/150/210 inches
Wand	Dual-jet stainless S-bend
Hose Assembly	25 ft.
Tank Construction	Polyethylene
Baseplate	¼" aluminum
Rear Wheels	10 inches, non-marking
Casters	4 inches
Power Cord	50 ft. detachable
Dimensions	37"H x 36"L x 19"W
Weight	78/ 95/97/101/112 lbs.
Shipping Weight	116/123/125/127/142 lbs.
Ship Dimensions	40" x 39" x 22"

\*For heated units, add 14 lbs. to ship weight

## WARRANTY

6 years on tank, 1 year on parts and labor