

**MATERIAL SAFETY DATA SHEET**

CHEMSPEC ® • 901 N. NEWKIRK STREET • BALTIMORE, MD 21205 • (410) 675-4800

HEALTH = 1, FLAMMABILITY = 2, REACTIVITY = 0, SPECIAL = NONE, DEGREE OF HAZARD: 4 = EXTREME, 3 = HIGH, 2 = MODERATE, 1 = SLIGHT, 0 = INSIGNIFICANT

PRODUCT NAME: **COLORFAST EXTRACTION UPHOLSTERY CLEANER**

DOCUMENT CODE: Colorfast Extraction Upholstery Cleaner

CHEMICAL FAMILY: Mixture

DATE: 10/09/97

DATE REVIEWED: 08/16/99

**EMERGENCY 24-HOUR TELEPHONE # 1-800-424-9300 (CHEMTREC)**

N/A = Not applicable

N/D = Not determined

**SECTION I: HAZARDOUS INGREDIENTS/HEALTH HAZARD DATA**

This product has not been tested as a whole for health effects on animals or humans. According to the OSHA Hazardous Communications Standard (29 CFR 1910.1200) any hazardous ingredients that comprise >1.0% of the material and any carcinogenic ingredients that comprise >0.1% must be listed on the MSDS.

**SECTION I (a): List of carcinogenic ingredients at >0.1%.**

None.

**SECTION I (b): List of hazardous ingredients at >1.0%.**

NAME	CAS NO.
2-BUTOXYETHANOL	111-76-2
ALCOHOL ETHOXYLATES	68439-50-9
1-METHOXY-2-PROPANOL	107-98-2

May cause eye irritation and corneal injury. May cause skin irritation. Prolonged or repeated dermal exposure may lead to hemolysis. Ingestion may lead to hemolysis and kidney effects. Inhalation may cause irritation to upper respiratory tract, blood and kidney effects. Oral rat LD50 is 470 mg/kg; dermal rabbit LD50 is 220 mg/kg; rat LC50 is 700 ppm in 7 hrs. OSHA PEL and ACGIH TLV are 25 ppm, skin.

May cause eye and skin irritation. Ingestion may cause abdominal discomfort, nausea and diarrhea. Oral rat LD50 is 2-5 mg/kg; dermal rabbit LD50 is 1-3 g/kg. OSHA PEL and ACGIH TLV not available.

May cause temporary eye injury. May irritate skin. Dermal absorption may cause drowsiness. Vapors may cause eye, nose and throat irritation.

Inhalation of concentrations >1000 ppm may have anesthetic effects. Overexposures may lead to liver and kidney effects. Oral rat LD50 is 6 g/kg; dermal rabbit LD50 is 11 g/kg. OSHA PEL and ACGIH TLV not available.

**SECTION II: EMERGENCY AND FIRST AID PROCEDURES**

EYES: Flush with water for at least 15 minutes. Consult physician.  
SKIN: Remove contaminated clothing. Thoroughly wash with soap and water.  
INHALED: Remove to fresh air. If symptoms persist consult physician.  
INGESTION: Drink 2 glasses of water and induce vomiting. Seek medical attention.  
PHYSICIAN: Treatment based on judgment of attending physician.

**SECTION III: PHYSICAL / CHEMICAL DATA**

APPEARANCE AND ODOR: Clear golden yellow liquid with mild solvent odor.

WATER SOLUBILITY, % BY WT: Approximately 98

WT/GAL: 8.0 lbs.

BOILING POINT: N/D

VOLATILE BY WT: 92 - 97

pH: 3.5 - 4.0

pH @ USE: 3.0 - 4.0

SPECIFIC GRAVITY: 0.95 - 0.96

**SECTION IV: FIRE AND EXPLOSION DATA**

FLASH POINT: 124 degrees F (TCC) AUTO-IGNITION TEMPERATURE: N/D

EXPLOSIVE LIMITS - LEL: N/D UEL: N/D

EXTINGUISHING MEDIA: Water fog, CO<sub>2</sub>, dry chemical and foam.

SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH/MSHA approved self-contained positive-pressure breathing apparatus and protective clothing where this material is involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

**SECTION V: REACTIVITY DATA**

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS: Possibly aldehydes, ketones, unidentified organic compounds, oxides of carbons, sulfur and nitrogen.

**SECTION VI: SPILLS, LEAKS AND DISPOSAL PROCEDURES**

WASTE DISPOSAL: In accordance with Federal, State and Local regulations.

NEUTRALIZING CHEMICALS: Lime

**SECTION VII: PROTECTION MEASURES**

VENTILATION: Local exhaust or dilution ventilation may be necessary in poorly ventilated areas.

EYE PROTECTION: Chemical resistant safety glasses.

RESPIRATORY PROTECTION: When adequate ventilation cannot be achieved or if individual may be sensitive to material, use NIOSH/MSHA approved respirator equipped with organic vapor cartridges.

GLOVES: Rubber gloves. OTHER PROTECTIVE EQUIPMENT: Body-covering clothing should be worn.

**SECTION VIII: SPECIAL PRECAUTIONS**

One should always use chemicals with awareness of potential hazards, known and unknown, and their effect on the human system. We urge users to minimize employee exposure to all chemicals, including this product and to keep the level of exposure commensurate with good industrial hygiene practices.

**DISCLAIMER OF LIABILITY**

The manufacturer and seller warrants that this product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.

Rev#: 8