

Material Safety Data Sheet

HMIS®

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HEALTH	2	REACTIVITY	0
FLAMMABILITY	1	PERSONAL PROTECTION	B

Identity (As Used on Label and List)

21416, 21420

Lemon Furniture

Polish

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION I

Manufacturer's Name

ITW Dymon

Emergency Telephone Number

800.535.5053

Address (Number, Street, City, State, and ZIP Code)

805 East Old 56 Highway

Telephone Number for Information

913.397.9889

Olathe, Kansas 66061

Date Prepared

August 31, 2001

Signature of Preparer (Optional)

Regulatory Dept.

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH-TLV	Other Limits Recommended	% (Opt)
Isoparaffinic hydrocarbons	64742-47-8	5 mg/m ³ (mist)	5 mg/m ³ (mist)		7 - 13 %
Isobutane	75-28-5	800 ppm	800 ppm		10 - 30 %
Propane	74-98-6	1000 ppm	Asphyxiant		1 - 5 %
White Mineral oil	8042-47-5	5 mg/m ³ (mist)	5 mg/m ³ (mist)		10 - 30 %

This product does not contain any chemical listed or present in concentrations requiring reporting under SARA Title III Sec. 313.

TSCA: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

SECTION III Physical/Chemical Characteristics

Boiling Point Concentrate	212°F	Specific Gravity (H₂O = 1) Concentrate	0.934
Pressure (psig. @ 70° F)	55±5	Melting Point	No Data
Vapor Density (AIR = 1)	No Data	Evaporation Rate (Butyl Acetate = 1)	No Data
Solubility in Water	Complete	pH	Not Applicable

Appearance and Odor -

Clear colorless liquid with a lemon scent in an aerosol can

SECTION IV - Fire and Explosion Hazard Data

USA Flame Projection Test (ASTM D-3065) 0", no flashback; Not flammable	Flammable Limits No Data	LEL No Data	UEL No Data
---	------------------------------------	-----------------------	-----------------------

Extinguishing Media -

Not usually necessary as this product does not readily support combustion. Use media appropriate for fire's fuel source.

Special Fire Fighting Procedures - Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

Unusual Fire and Explosion Hazards -

Aerosol container (pressurized) may burst if heated over 130° F.

SECTION V - Reactivity Data

Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	

Incompatibility (Materials to Avoid) -

Strong oxidizers, aluminum, galvanized iron and zinc.

Hazardous Decomposition or Byproducts -

Carbon dioxide, carbon monoxide and various organic oxidation products.

Hazardous Polymerization	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	

SECTION VI - Health Hazard Data

Route(s) of Entry	Eyes?	Inhalation?	Skin?	Ingestion?
	Yes	No	Yes	Yes

Health Hazards (Acute and Chronic) - Warning. Causes eye irritation. Harmful if inhaled or swallowed. May cause skin and respiratory tract irritation. Contains petroleum distillates. Overexposures may induce central nervous system effects. Repeated or prolonged occupational overexposure may induce dermatitis or Painter's Syndrome. Aspiration hazard if swallowed. Follow good chemical hygiene practices when using this and other alkaline butyl cleaning compounds.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
None known	No	No	No

Signs and Symptoms of Exposure - Stinging, tearing, redness or burning in eyes. Redness, burning, dryness or cracking skin. Nose and throat irritation. May cause irritation of the digestive tract.

Medical Conditions Generally Aggravated by Exposure

Pre-existing lung, blood, liver or kidney disorders may be adversely affected.

Emergency and First Aid Procedures: Eyes - Flush with plenty of water for at least 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention. **Ingestion -** Do not induce vomiting, contains petroleum distillates. . If conscious, wash out mouth with water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Inhalation - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. **Skin -** Flush with plenty of water for at least 15 minutes. If irritation arises and persists, call a physician.

SECTION VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled - Caution, slip hazard. Wipe up small spills promptly with a rag or other absorbant material. For large spills, isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Pick up with an absorbant material and put in suitable container for proper disposal.

Waste Disposal Method - Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.

Precautions to be Taken in Handling and Storing - Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid inhaling mist or vapors. Wash thoroughly after handling. Do not swallow. Store in a cool (under 120° F) dry location away from heat, sparks, open flame, and direct sunlight.

Other Precautions - Follow label directions carefully. Keep out of reach of children. Do not deliberately concentrate and inhale vapors. Direct spray away from face. Replace cap when not in use. Do not smoke while using. Do not use around ignition sources such as heat, sparks, open flame, etc. Do not puncture or incinerate container.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type) - Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH\MSHA respirator.

Ventilation	Local Exhaust	Not usually needed	Special	None
	Mechanical (General)	Yes	Other	None

Protective Gloves -

Yes, impervious

Eye Protection -

Yes, goggles or approved safety glasses (ANSI Z87)

Other Protective Clothing or Equipment -

Not usually needed. If direct contact is possible, wear apron, boots, face shield, etc. as necessary.

Work/Hygienic Practices -

Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

WARNING: The use of this product is beyond the control of the manufacturer, therefore, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established user must assume all responsibility, including injury or damage.
 HAS TO DESCRIPTION, QUALITY,
 MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. The sole and exclusive remedy against the manufacturer for
 breach of PERSON
 OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.