

Material Safety Data Sheet

HMIS®

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HEALTH

3

REACTIVITY

0

FLAMMABILITY

1

PERSONAL PROTECTION

B

Identity (As Used on Label and List)

34620

Baseboard Stripper

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION I

Manufacturer's Name ITW Dymon	Emergency Telephone Number 1-800-535-5053
Address (Number, Street, City, State, and ZIP Code) 805 East Old 56 Highway	Telephone Number for Information 1-913-397-9889
Olathe, Kansas 66061	Date Prepared April 3, 2000
	Signature of Preparer (Optional) Regulatory Dept.

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH-TLV	Other Limits Recommended	%(Opt.)
Isobutane	75-28-5	800 ppm	800 ppm		7 - 13 %
2-Aminoethanol	141-43-5	3 ppm	3 ppm	STEL - 6 ppm	1 - 5 %
*2-Butoxyethanol	111-76-2	50 ppm**	25 ppm**		1 - 5 %
Propane	74-98-6	1000 ppm	Asphyxiant		1 - 5 %

*2-Butoxyethanol (a glycol ether compound) may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. Refer to 40 CFR 372. This information must be included in all MSDSs that are copied and for this material.

** - Skin designation

TSCA: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

SECTION III Physical/Chemical Characteristics

Boiling Point Concentrate	212° F	Specific Gravity (H₂O = 1) Concentrate	1.043
Pressure (psig. @ 70° F)	60 ± 5	Melting Point	No Data
Vapor Density (AIR = 1)	Greater than one (1)	Evaporation Rate (Butyl Acetate = 1)	No Data
Solubility in Water Complete		pH	13 ± 0.5

Appearance and Odor

Opaque tan liquid with an ethereal scent in an aerosol can.

SECTION IV - Fire and Explosion Hazard Data

USA Flame Projection Test 3" - No Flashback - Nonflammable	Flammable Limits No Data	LEL No Data	UEL No Data
--	------------------------------------	-----------------------	-----------------------

Extinguishing Media -

Not usually necessary as this product does not readily support combustion. Use extinguishing agent suitable to fuel source.

Special Fire Fighting Procedures - Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

Unusual Fire and Explosion Hazards -

Aerosol container (pressurized) may burst if heated over 120° F.

SECTION V - Reactivity Data

Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	

Incompatibility (Materials to Avoid)

Strong oxidizers, acids, aluminum, tin, lead, zinc.

Hazardous Decomposition or Byproducts

Carbon dioxide, carbon monoxide, oxides of nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	

SECTION VI - Health Hazard Data

Route(s) of Entry	Eyes? Yes	Inhalation? Yes	Skin? Yes	Ingestion? Yes
-------------------	--------------	--------------------	--------------	-------------------

Health Hazards (Acute and Chronic) -

Danger: Corrosive. May be harmful or fatal if swallowed. Causes burns to eyes and skin with direct contact. May cause respiratory tract irritation. May be absorbed through intact skin. Central nervous system effects may be induced if used with improper ventilation. Use proper chemical hygiene to avoid these hazards.

Carcinogenicity: None known.	NTP? No	IARC Monographs? No	OSHA Regulated? No
---------------------------------	------------	------------------------	-----------------------

Signs and Symptoms of Exposure -

Burning or tearing in eyes. Irritation of nose and throat. Redness, irritation or slick feeling on skin. Nausea, loss of coordination, fatigue.

Medical Conditions Generally Aggravated by Exposure -

Pre-existing skin and lung disorders (i.e. - asthma) can be effected by prolonged or repeated occupational overexposure.

Emergency and First Aid Procedures: -

Eyes - Flush with plenty of water for at least 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention.

Ingestion - DO NOT induce vomiting unless directed by a physician. If conscious, rinse out mouth with water, then give large quantities of water and seek immediate medical attention. Never give anything by mouth to an unconscious person.

Inhalation - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration.

Skin - Flush with plenty of water for at least 15 minutes. If irritation arises and persists, seek medical attention.

SECTION VII - Precautions for Safe Handling and Use**Steps to be Taken in Case Material is Released or Spilled -**

Isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Do not allow material to enter sewers or drains. Pick up on absorbent or use vacuum. Put in suitable container. Dispose of properly.

Waste Disposal Method -

Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.

Precautions to be Taken in Handling and Storing - Do not get in eyes, on skin or clothing. Wash thoroughly after handling. Launder contaminated clothing before reuse. Store in a cool (under 120° F) dry location away from heat, sparks, open flame, and direct sunlight. Direct spray away from face. Replace cap when not in use. Avoid inhaling mist or vapors.

Other Precautions - Follow label directions carefully. Keep out of reach of children. Do not deliberately concentrate and inhale vapors. Do not inhale mist or vapors. Do not swallow. Use with adequate ventilation.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type) - Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH\MSHA respirator.

Ventilation	Local Exhaust	Satisfactory	Special	None
	Mechanical (General)	Yes	Other	None

Protective Gloves Impervious	Eye Protection Safety glasses or goggles (ANSI Z87)
---------------------------------	--

Other Protective Clothing or Equipment - As needed to protect against all skin contact. (i.e. - apron, boots, etc.)

Work/Hygienic Practices - Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

WARNING! The use of this product is beyond the control of the manufacturer; therefore, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The user must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.
The manufacturer warrants only that this product meets the manufacturer's specifications for such product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. The sole and exclusive remedy against the manufacturer for breach of warranty shall be reimbursement of the purchase price of the product in the event that a defective condition of the product shall be found to exist. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.