

MATERIAL SAFETY DATA SHEET - U.S.

Dry Cleaning Compound B137

Professional Chemicals Corporation

Revision Date: August 8, 2001 Revision 2.0

Section 1: Chemical Product and Company Information

Product Name: Dry Cleaning Compound

Product Number: B137

Manufacturer: Professional Chemicals Corp
325 S. Price Road
Chandler, AZ USA 85224

Emergency Telephone:
(800) 535-5053 [Infotrac]

Section 2: Composition / Information or Ingredients

<u>Hazardous Ingredient</u>	<u>CAS</u>	<u>OSHA PEL</u>	<u>OSHA HAZARD</u>
Odorless Mineral Spirits	64742-48-9	N/E	Irritant/Flammable

Section 3: Hazard Identification

Emergency Overview

Appearance: Clear Liquid

Odor: Citrus Scent

Flashpoint: 120°F

Hazard: Combustible liquid.

Eye Contact: May cause temporary eye irritation; injury to eye tissue unlikely

Skin Contact: Frequent or prolonged contact may cause temporary irritation. Skin contact may aggravate an existing dermatitis condition.

Inhalation: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, drowsiness, and other central nervous system effects.

Ingestion: Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.

HMIS Hazard Rating: Health 2 Flammability 2 Reactivity 0

Section 4: First Aid Measures

Eye Contact: Immediately irrigate with flowing water continuously for 15 minutes. If irritation persists consult medical personnel.

Skin Contact: Wash with soap and water. If irritation persists consult medical personnel.

Inhalation: Move to fresh air. If irritation persists consult medical personnel.

Ingestion: If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

MATERIAL SAFETY DATA SHEET - U.S.

Dry Cleaning Compound B137

Professional Chemicals Corporation

Revision Date: August 8, 2001 Revision 2.0

Section 5: Fire-Fighting Measures

Flashpoint: 120°F (closed cup)

Upper Flammable Limit (% by volume): 9.8%

Autoignition Temperature: 660°F

Lower Flammable Limit (% by volume): 1.3%

General Hazard: Combustible liquid.

Fire Fighting Procedures: Wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to fire.

Hazardous Decomposition Products: During a fire, smoke may contain the original material in addition to unidentified toxic and/or irritating compounds. Hazardous combustion products may include and are not limited to carbon dioxide and carbon monoxide.

Section 6: Accidental Release Measures

Keep all unnecessary personnel away. Eliminate sources of ignition. Prevent additional discharge of material. Prevent material from entering sewers, watercourses, or low areas. Contain and absorb spilled material with sand or earth. Do not use combustible materials such as sawdust. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Section 7: Handling and Storage

Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or alkaline products and ignition sources. Cloths used to apply or absorb product should be rinsed with water and stored in a fire-resistant container. Avoid contact with skin and eyes. Use in a well-ventilated area; do not breathe vapors. Wash hands thoroughly after handling.

Section 8: Exposure Controls / Personal Protection

Engineering Controls: Normal room ventilation is satisfactory for limited use; keep away from heat and flame.

Eye Protection: Safety glasses

Skin Protection: Use gloves impervious to this material when prolonged or frequently repeated contact could occur.

Respiratory: Where concentrations in air may exceed the limits given in Section 2 and engineering, work practice or other means of exposure reduction are not adequate, NIOSH/OSHA approved respirators may be necessary to prevent overexposure by inhalation.

Exposure guidelines: N/E

MATERIAL SAFETY DATA SHEET - U.S.

Dry Cleaning Compound B137

Professional Chemicals Corporation

Revision Date: August 8, 2001 Revision 2.0

Section 9: Physical and Chemical Properties

Appearance/Physical State: Clear Liquid

Vapor Pressure: 1 mm/Hg @ 68°F

Boiling Point: 354-372°F

Density: 6.3 lbs. /gal.

Solubility in Water: <0.01 % @ 77°F

Odor: Citrus scent

Vapor Density: N/D

Freezing Point: <-76°F

Concentrate pH: N/A

RTU pH: N/A

Section 10: Stability and Reactivity

Chemical stability: Stable

Incompatibility with other substances: Strong oxidizing or alkaline agents

Reactivity: None known.

Hazardous Decomposition Products: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.

Section 11: Toxicological Information

Route of Entry: Eye contact, Skin absorption/contact, Inhalation and Ingestion

Effects of Acute Overexposure to Product:

Eye Contact: May cause temporary eye irritation, redness, tearing, and blurred vision

Skin Contact: May cause temporary skin irritation, defatting and dermatitis

Inhalation: Inhalation of mist or vapor may cause temporary respiratory irritation; temporary central nervous system effects including dizziness, weakness, fatigue, nausea, and headache.

Ingestion: May cause gastrointestinal temporary irritation with nausea, vomiting and diarrhea
aspiration into the lungs can cause chemical pneumonitis.

Effects of Chronic Overexposure to Product:

Exposure limits: N/D for mixture

Teratogenicity: None

Reproductive toxicity: None

Sensitization to Product: None known

Mutagenicity: None

Carcinogenicity: None

Section 12: Ecological Information

Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

Section 13: Disposal Considerations

Dispose of in accordance with federal, state and local regulations. Prevent run-off to sewers.

MATERIAL SAFETY DATA SHEET - U.S.

Dry Cleaning Compound B137

Professional Chemicals Corporation

Revision Date: August 8, 2001 Revision 2.0

Section 14: Transportation Information

Shipping paper description: Petroleum Distillate, N.O.S.

Labeling: Combustible Liquid

Markings: Petroleum Distillate, N.O.S.

Placard: NONE-EXEMPT

Packaging: Inner package not over 5.0 liters (1 gallon) each, in strong outer packaging. UN specification packaging not required.

Note: In containers of 119 gallons capacity or less this product is not regulated by DOT. Applies only to ground shipments. Additional compliance steps are required for air shipments. Ship in accordance with 49 CFR parts 100 - 185.

Section 15: Regulatory Information

TSCA: All chemicals used in this product are listed

CERCLA: No

SARA Title III: Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the immediate health hazard category.

The chemicals used in this product may be subject to the provisions of the Community Right-to Know Act (40 CFR 370 - 374). If reporting requirements are met, please contact the Environmental, Health and Safety (EHS) Manager for information regarding this product.

Section 16: Other Information

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000